


An Assessment on the Existing Flood Mitigation System in Village East Executive
Homes, Cainta, Rizal Using the Rational Method

A Research Presented to Faculty of Civil Engineering
College of Engineering, Architecture, and Technology

De La Salle University – Dasmariñas

Dasmariñas City



In Partial Fulfillment of Requirements for the Course
Bachelor of Science in Civil Engineering

Submitted by:

Wellabelle M. Cuarto

Josen Brian O. Laserna

Nizza Mariel O. Zacarias

CEE51

October 2011

Abstract

This study was intended to assess an existing flood mitigation system for the Village East Cainta Rizal by using the rational method. For this purpose, the researchers gathered data such as rainfall intensity data, location, topographical and land use data and made use of empirical models. Based from the computations made by the researchers, the existing drainage system of the village is unable to accommodate the entire runoff entering the village. The results of the computations presented, showing the flow velocity, flow capacity and the accumulated flow of the existing design can help the Homeowners' Association of Village East Cainta Rizal to further improve their drainage system. They can be also helped in their planning activities relating to the community-level flood-mitigation and disaster response. A program of pipe sizes and discharge flows are also available for use as a guide for their maintenance of their drainage canals.

Table of Contents

	Page No.
Approval Sheet	ii
Abstractiii
Acknowledgement	iv
Chapter 1 The Problem and Its Background	
1.1 Introduction	1
1.2 Statement of the Problem	2
1.3 Research Objectives	3
1.4 Scope and Limitations	3
1.5 Significance of the Study	4
1.6 Study Framework	5
1.7 Definition of Terms	6
Chapter 2 Review of Related Literature	
2.1 Project Description	7
2.2 Return Period	9
2.3 Rational Method and Surface Runoff	8
2.4 Precipitation	11
2.5 Rainfall Intensity	11
2.6 Time of Concentration	12
2.7 Seelye Chart Method	12
2.8 Kirpitch Chart	13
2.9 Minor Losses in Pipelines	14
2.10 The Hazen – Williams Equation	15
2.11 Uniform Flow and Continuity equation	17
2.12 Manning’s Equation	17
2.13 Coefficient of imperviousness	18
2.14 Manhole Spacing	19

2.15	Design Standards and Considerations for Storm Drain Pipe Systems	19
2.16	Commercial Reinforced Concrete Pipe Sizes	21
Chapter 3 Methodology		
3.1	Analytical Framework	22
3.2	Data Gathering	23
3.3	Data Analysis	24
Chapter 4 Data Presentation and Analysis		
4.1	Data Presentation	25
4.1.1	Summary of Adapted Parameters	24
4.1.2	Summary of Peak Runoff	26
4.1.3	Summary of Peak Flow and Maximum Capacities	27
4.2	Data analysis	27
4.3	Data Results	28
Chapter 5 Conclusion and Recommendation		
5.1	Conclusion	29
5.2	Recommendations	29
Appendices.		
	Appendix A. Maps, Plans and Charts used	35
	Appendix B. Secondary Data and Results	48
	Appendix C. Sample Computations	49
	Appendix D. Documentation (photos)	80
	Appendix E. Approved Letters.	91
Bibliography		97

List of Tables and Figures

Table No.	Title	Page No.
2.1	Runoff Coefficient for $Q_p=C_iA$ equation	10
2.2	Rainfall Intensity Classification	11
2.3	Minor Losses in Pipelines	16
2.4	Values of Hazen – Williams Coefficient	17
2.5	Manning’s Roughness Coefficient	19
2.6	Impervious Coefficient Values	20
4.1	Adapted Standards and Design Parameters.	25
4.2	Summary of Peak Runoff	27
4.3	Summary of Peak Flow and Maximum Capacities	28
4.4	Summary of Data Results	29
6.1	Summary of Peak Flow and Maximum Capacities (English Unit)	47
6.2	Computation for Average Runoff	48
6.3	Area Computation	49
6.4	Sample Computations for a pipe network of Granada Street	57
6.5	Flow Capacity Computation (Drainage A)	60
6.6	Flow Capacity Computation (Drainage B)	71
6.7	Computation for Resizing (Drainage A)	77
6.8	Computation for Resizing (Drainage B)	79

Figure No.	Title	Page No.
1.1	Study Framework of the Study	5
2.1	Topographical Map of Area Considered	8
2.2	Seelye Chart	14

2.3	Kirpitch Chart	15
3.1	Methodological Method	23
4.1	Recommended Pipe resizing for Drainage A	30
4.2	Recommended Pipe resizing for Drainage B	31
6.1	Topographical Map of the Area to be considered	35
6.2	Drainage Plan of Village East Executive Homes	36
6.3	Drainage water flow in Village East Executive Homes	37
6.4	Map of Flooded Areas	38
6.5	Corrections on Relation Based on the Actual Topographical Survey	39
6.6	Areal Computation Figure	40
6.7	Flow Paths/Hydraulic Lengths.	41
6.8	Seelye Chart for Computation of Travel Time Overland Flow	42
6.9	Diagram for Computing the Average Velocity of Shallow Concentrated Flow	43
6.10	Kirpitch Chart	44
7.1	Pipe system of Granada Street	52
7.2	Definition Sketch for pipe flow	52
8.1	Hydraulic gradient familiarization in DPWH-Masinag Antipolo City	80
8.2	Gathering data for rainfall intensity from PAGASA	80
8.3	Village East Executive Homes Association's Office and Site Map	81
8.4	Roads along Drainage A and Drainage B respectively	81
8.5	Verification of drainage size in pipe line of drainage B along Cougar St (18" \emptyset pipe)	82
8.6	Outflow point of drainage A and B respectively	82
8.7	Drainage A along Village East Avenue	83
8.8	Drainage A for Daytona St. and Escort St. respectively	83
8.9	Drainage A for Bentley St. and BMW St. respectively	84

8.10	Drainage A along Village East Avenue corner of Corona St. and Corolla St. respectively	84
8.11	Drainage B for Crown St. and Corona St. respectively	85
8.12	Drainage B for Cougar St. and Celica St. respectively	85
8.13	Drainage B for Charger St. and Champ St. respectively	86
8.14	Drainage B for Corolla St. and Citroen St. respectively	86
8.15	Drainage B for Caprice St. and Cobra St. respectively	87
8.16	Drainage B for Courier St. and Charger St. respectively.	87
8.17	Shot A (corner of Corona St. and Village East Drive)	88
8.18	Shot B (near BMW Street)	88
8.19	Shot C (corner of Daytona St. and Dasher St.)	89
8.20	Shot D (corner between Escort St. and Crown St.)	89
8.21	Shot E (corner near Ferrari St. and Vista Verde Ext.)	90
8.22	Shot F (corner of Fiero and Fiat St.)	90

