


**Microcontroller Unit - Based Rain Gauge
With Global System for Mobile Communications**

A Project Study Presented to
The Faculty of Electronics Engineering
De La Salle University – Dasmariñas



In Partial Fulfillment
Of the Requirement for the Degree
Bachelor of Science major
In Electronics and Communications Engineering

Bacanto, Gene Psyche M.

Cortez, Martin Xavier T.

Ebron, Romgie T.

Labosta, Edmark I.

Macapagal, Roven Joseph F.

March 2012

ABSTRACT

Title: Microcontroller Unit – based Rain Gauge with Global System for Mobile Communications

Researchers:

Bacanto, Gene Psyche M.

Cortez, Martin Xavier T.

Ebron, Romgie T.

Labosta, Edmark I.

Macapagal, Roven Joseph F.

The Rain Gauge is an instrument for gathering and measuring the amount of rainfall that a storm drops during its precipitation. It is one of the measuring tools that observers in PAGASA use to gather rainfall data needed to create weather forecasts. Despite the advancement in modern technology, many countries including the Philippines still use the manual measuring tool because of its accuracy. In order to create an accurate forecast, observers gather data from multiple rainfall depth measuring devices and compare them all using the computers installed at the PAGASA forecasting department. The drawback of using the manual rain gauge is the danger that it imposes on the observer that will use it. When a storm is present, the observer may be exposed to lightning strikes and heavy rain.

This study aims to aid PAGASA by creating a device that will measure rainfall depth on a certain location and will automatically send the information on a set interval via SMS. Upon the completion of the said device, the observer will no longer subject himself to environmental hazards during rainfall depth measurement. A Microcontroller Unit will be used to control all the processes in rainfall depth measurement, namely water level sensing, motor control, draining via solenoid valve and sending information using the GSM module. The researchers will test the said device by simulating artificial rain.



Table of Contents

	Pages
Title Page	i
Approval Sheet	ii
Acknowledgement	iii
Abstract	v
Table of Contents	vii
List of Figures	x
List of Tables	xii
Chapter I. The Problem and its Background	
Background of the Study	1
Statement of the Problem	2
Research Objectives	3
Conceptual Framework	5
Scope and Limitations of the Study	6
Significance of the Study	7
Definition of Terms	8
Chapter II. Review of Related Literatures and Studies	
Foreign Literature	10
Foreign Studies	15
Local Literature	29
Local Studies	35

Relevance of the Study	38
------------------------	----

Chapter III. Research Methods and Procedures

Research Methods	40
------------------	----

Research Instruments	41
----------------------	----

Data Gathering Procedure	42
--------------------------	----

Data Analysis	44
---------------	----

System Design	44
---------------	----

Determination of dimensions of the proposed rain gauge	44
--	----

Determination of materials to be used	45
---------------------------------------	----

Experimentation	45
-----------------	----

Testing	46
---------	----

Reliability Test	46
------------------	----

Functionality Test	46
--------------------	----

Accuracy Test	47
---------------	----

Acceptability test	47
--------------------	----

Operational Flowchart	48
-----------------------	----

Proposed System Layout	49
------------------------	----

Chapter IV. Presentation, Analysis and Interpretation of Data


System Operation	51
------------------	----

Reliability Test Evaluation	54
-----------------------------	----

Functionality Test Evaluation	59
-------------------------------	----

Accuracy Test Evaluation	67
--------------------------	----

Acceptability Test Evaluation	70
-------------------------------	----



Final System Layout	71
Prototype Design	75
Mechanical Design	75
Electrical Design	80
Chapter V. Summary, Conclusion and Recommendations	
Summary	89
Conclusion	90
Recommendation	91
Implications	92
Appendices	93
Appendix A - Formal Letters	94
Appendix B - Research Photographs	107
Appendix C - Gantt Chart	116
Appendix D - Program Proper	117
Appendix E - Components Data Sheet	131
Appendix F - Résumé	162
Appendix G - User's Manual of MCU based Rain Gauge with GSM	176
Appendix H - Materials Used	183
Appendix I - Certificates	186
Appendix J - Survey Forms	192
Appendix K - References	197

List of Figures

Figure 1.1 Research Paradigm	5
Figure 2.1 Cooperative weather station at Granger, Utah in 1930	14
Figure 2.2 Hooke's self-recording rain-gauge	14
Figure 2.3 General architecture of the GSM Network	24
Figure 2.4 Signaling protocol structure in GSM	26
Figure 2.5 Non-recording, 8-inch rain-gauge	35
Figure 2.6 MCU based flood monitoring system	36
Figure 3.1 Automated Rain Gauge's Operational Flowchart	48
Figure 3.2 Proposed System Layout	50
Figure 4.1 Process Flow for 6-hour Observation	52
Figure 4.2 Process Flow for Filled-up Rain Gauge	53
Figure 4.3 Process Flow for Rainfall Depth Status Inquiry	53
Figure 4.4 1st Periodic Report of Reliability Test	54
Figure 4.5 2nd Periodic Report of Reliability Test (Periodic Report)	55
Figure 4.6 3rd Periodic Report of Reliability Test	56
Figure 4.7 Final Periodic Report of Reliability Test	56
Figure 4.8 Bar Graph of Reliability test for 1st 6 hours	57
Figure 4.9 Bar Graph of Reliability test for 2nd 6 hours	57
Figure 4.10 Bar Graph of Reliability test for 3rd 6 hours	58
Figure 4.11 Bar Graph of Reliability test for final 6 hours	58
Figure 4.12 Actual Boot-up Report for Light Rainfall Category	60

Figure 4.13 Actual Inquiry Report for Light Rainfall Category – 2 hours	60
Figure 4.14 Actual Inquiry Report for Light Rainfall Category – 4 hours	61
Figure 4.15 Actual Result of Varying Water Level – Light Rainfall (Periodic Report)	61
Figure 4.16 Graph of Varying Water Level – Light Rainfall Category	62
Figure 4.17 Actual Boot-Up Report for Moderate Rainfall Category	62
Figure 4.18 Actual Inquiry Report for Moderate Rainfall Category – 2 hours	63
Figure 4.19 Actual Inquiry Report for Moderate Rainfall Category – 4 hours	63
Figure 4.20 Actual Result of Varying Water Level – Moderate Rainfall (Periodic Report)	64
Figure 4.21 Graph of Varying Water Level – Moderate Rainfall Category	64
Figure 4.22 Actual Boot-up Report for Heavy Rainfall Category	65
Figure 4.23 Actual Inquiry Report for Heavy Rainfall Category – 2 hours	65
Figure 4.24 Actual Inquiry Report for Heavy Rainfall Category – 4 hours	66
Figure 4.25 Actual Result of Varying Water Level – Heavy Rainfall (Periodic Report)	66

Figure 4.26 Testing Day 7: Varying Water Level – Heavy Rainfall	
Category	67
Figure 4.27 The Researchers Together with Mr. Ferdinand Barcenas (in green shirt)	68
Figure 4.28 Final System Layout	71
Figure 4.29 Comparing of the Water Level Inside and Outside of the Rain Gauge	73
Figure 4.30 Water Level Magnified by 150 times	74
Figure 4.31 Actual Fabricated Acrylic Catchment	76
Figure 4.32 Actual Fabricated Acrylic Container	77
Figure 4.33 Actual Fabricated Wooden Housing	78
Figure 4.34 Actual 12-volt battery used	78
Figure 4.35 Actual Circuit Mounted on the Plastic Housing	79
Figure 4.36 Actual Windshield Washer Pump	79
Figure 4.37 Actual Probes for Water Level Sensor	80
Figure 4.38 Schmitt trigger Sensor Schematic Diagram	80
Figure 4.39 Simulated Schmitt Trigger Sensor (without continuity)	81
Figure 4.40 Simulated Schmitt Trigger Sensor – gradual increase in water level	82
Figure 4.41 Circuit Layout of Schmitt Trigger Water Level Sensor	82
Figure 4.42 MCU and Power Supply Circuit Schematic Diagram	83
Figure 4.43 Schematic Diagram of MCU and Power Supply Circuit	83
Figure 4.44 Schematic Diagram of GSM Module	84

Figure 4.45 Circuit Layout of GSM Module	84
Figure 4.46 Example of a Boot-up Report SMS	85
Figure 4.47 Example of a Periodic Report SMS	86
Figure 4.48 Example of an Inquiry Report SMS	86
Figure 4.49 Example of an Inquiry Command SMS	87
Figure 4.50 Schematic diagram of Relay Circuit	88
Figure 4.51 Circuit layout of Relay Circuit	88

List of Tables

Table 4.1 Standard Rainfall Categories from PAGASA	59
--	----

