

UNIVERSITY LIBRARY USAGE MONITORING SYSTEM

A Project Study

Presented to

the Faculty of the College of Engineering, Architecture and Technology

De La Salle University – Dasmariñas

Dasmariñas, Cavite

In Partial Fulfillment

of the Requirement for the Degree of

Bachelor of Science in Electronics and Communications Engineering

CANZON, Gene Joseph M.

CARIAGA, Francois Q.

DIMARANAN, Kristian C.

ESTIALBO, Kean G.

February 2010

TABLE OF CONTENTS

TITLE PAGE	
ACKNOWLEDGEMENT	i
TABLE OF CONTENTS	ii
LIST OF FIGURES	iv
LIST OF APPENDICES	vi
ABSTRACT	vii
CHAPTER 1 – THE PROBLEM AND ITS BACKGROUND	
Introduction	1
Background of the study	2
Statement of the Problem	3
Significance of the Study	4
Conceptual Framework	5
Scope and Delimitation of the Study	6
Definition of Terms	8
CHAPTER 2 – REVIEW OF RELATED LITERATURES AND STUDIES	
Conceptual Literature	9
Related Studies	22
Synthesis	22
CHAPTER 3 – RESEARCH METHODOLOGY AND PROCEDURE	
Research Methodology	23
Data Gathering Procedure	24
Hardware Construction	25
Testing and Evaluation	36

CHAPTER 4 – PRESENTATION, ANALYSIS AND INTERPRETATION OF DATA

Project Description	37
Hardware Assembly	38
Software Development	44
Flow Presentation	44
Material Listing and Costing	46
Result of Evaluation and Testing	50


CHAPTER 5 – SUMMARY, CONCLUSION AND RECOMMENDATION

Summary	57
Conclusions	57
Recommendations	58

REFERENCES	59
-------------------	----

APPENDICES	61
-------------------	----

CURRICULUM VITAE	
-------------------------	--



LIST OF FIGURES

Chapter 1

Figure 1. Research Paradiagram Page 5

Chapter 2

Figure 2.1: Architecture of Sensor Node Page 13

Figure 2.2: Example of Photo Transistor Page 17

Figure 2.3: Example of Motion Detectors Page 18

Figure 2.4: Example of Passive Infrared Sensors Page 19

Figure 2.5: Barcode Sensors Page 21

Chapter 3

Figure 3.1: Main Controller Board, PCB Layout Page 26

Figure 3.2: PIC16f628a-based 7 segment decoder driver PCB Layout Page 26

Figure 3.3: 8x8 Dot-Matrix Display Driver PCB Layout Page 27

Figure 3.4: PIC16f628a-based 7 segment decoder PCB Layout Page 28

Figure 3.5: 8x8 Dot-Matrix Display PCB Layout Page 28

Figure 3.6: Sensor PCB Layout Page 29

Figure 3.7: Matrix Board Schematic Diagram Page 30

Figure 3.8: Main Controller Schematic Diagram Page 30

Figure 3.9: 7 Segment Schematic Diagram Page 31


Figure 3.10: Flow of Information Page 35

Chapter 4

Figure 4.1: University Library Usage Monitoring System Page 37

Figure 4.2: Main Controller, Actual Design Page 38

Figure 4.3: PIC16f628a-based 7 segment decoder extended	Page 39
Figure 4.4: 8x8 Dot-Matrix Displays Actual Design	Page 40
Figure 4.5: Photo / Laser Sensor Actual Circuit	Page 41
Figure 4.6: Testing of University Library Usage Monitoring System	Page 42
Figure 4.7: Actual Test and Implementation	Page 42
Figure 4.8: Troubleshooting of Display	Page 43
Figure 4.9: Actual Implementation	Page 43
Figure 4.10: Operation of the System	Page 44
Figure 4.11: Block Diagram of the System	Page 45
Figure 4.12: Annual result chart and database	Page 50
Figure 4.13: Daily result chart and database	Page 51
Figure 4.14: Monthly result chart and database	Page 51



List of Tables

Table 4.1: Materials Costing Table	Page 86
Table 4.2: Daily Result Table	Page 51
Table 4.3: Monthly Result Table	Page 52
Table 4.4: Annual Result Table	Page 55



List of Appendices

Materials Listings

PIC16F877a Data Sheet

PIC16f628a Data Sheet

MAX232 Data Sheet


74LS164 Data Sheet

74LS245 Data Sheet

7805 IC Data Sheet

Instruction Operation Manual for University Library Usage Monitoring System

Gantt Chart



ABSTRACT

TITLE: University Library Usage Monitoring System

RESEARCHERS: Canzon, Gene Joseph M.
Cariaga, Francois Q.
Dimaranan, Kristian C.
Estialbo, Kean G.

ADVISER: Engr. Emmanuel Longares

SCHOOL: De La salle University – Dasmariñas

PAGES: 185

YEAR: 2010

DEGREE: BS Electronics and Communications Engineering

The University Library Usage Monitoring System is a system that will enable library users to know the availability of the library. It will be composed of a display using 7 segment for the date, time and counter display, dot-matrix for the message display and microcontroller system that will control the operation and communication of the system. This will show the number of students currently using the library over the total capacity of the library. The decrementing parameter on the system will be by means of a sensor and the incrementing parameter would be by barcode scanner. Also, a statistical record can be withdrawn from the system that will show what college or department uses the library most. The statistical record, readable and printable, would be programmed using Visual Basic program. This will benefit both users and administrators by means of the display and the statistical record.