Dog Repeller with Stun Gun

A Project Study Presented to The faculty of Engineering De La Salle University- Dasmariñas

In partial fulfillment Of the requirements for the degree of Bachelor of Science in Electronics and Communications Engineering

> Co, Jayson E. Mebrano, Lovello G Perey, Glenn A.

> > ECE53

February 2008

Table of Contents

Approval Sheet	i
Acknowledgement	ii
Table of Contents	iv
Abstract	ix

Chapter I

Introduction	1
Background of the Study	2
Conceptual Framework	5
Statement of the Problem	5
Objectives	6
Significance of the Study	6
Scope and Delimitation of the Study	7
Definition of Terms	8

Chapter II

Conceptual Literature	9
Related Studies	12
Synthesis	17

Chapter III

Research	Methodology and	Procedure	18
----------	-----------------	-----------	----

Chapter IV

Presentation of Data	37
Analysis of Data	43

Interpretation	n of Data	44
----------------	-----------	----

Chapter V

Conclusion4	9
Recommendation4	9

References51

Curriculum Vitae	3
------------------	---



List of Tables

Chapter I	
Table 1 Different hearing frequency ranges of some	
animals	4
Chapter IV	
Table 4.1 Tests made to a Pit Bull	.37
Table 4.2 Tests made to a Rottweiler	.37
Table 4.3 Tests made to a Mongrel (Stray dog)	.37
Table 4.4 Tests made to a German shepherd	38
Table 4.5 Tests made to a Mongrel	.38
Table 4.6 Material Costing and Listing	.47

List of Figures

Chapter I	
	Figure 1 The research paradigm5
Chapter III	
	Figure 3.1 Block diagram of Dog repeller20
	Figure 3.2 Schematic Diagram of Stun Gun20
Chapter IV	
	Figure 4.1 Astable mode circuit diagram
	using 555 timer24
	Figure 4.2 Schematic diagram of dogrepeller using
	pic16f84a microcontroller26
	Figure 4.3 Schematic diagram of
	improvise stun gun
	Figure 4.4 Schematic diagram of an audio amplifier using
	LM 38627
	Figure 4.5 Two 555 timer circuit used as
	dog repeller28
	Figure 4.6 Breadboard design of dog repeller
	with single 555 timer IC29
	Figure 4.7 Square wave output
	during experimentation29
	Figure 4.8 Distorted waveform with
	44 KHz using 555 timer30
	Figure 4.9 Waveform with longer on state
	Figure 4.10 Top view of dog repeller
	using microcontroller32
	Figure 4.11 Circuit taken from Mosquito zapper40
	Figure 4.12 Modified mosquito zapper40

Figure 4.13 On state of the voltage doubler
circuit41
Figure 4.14 Off state of the voltage doubler circuit
Figure 4.15 Waveform of the voltage doubler
circuit42
Figure 4.16 Sample forum about dogs' hearing
ranges,



Abstract

Title	:	Dog Repeller with Stun Gun
Researchers	:	Co, Jayson E. Mebrano, Lovello G. Perey, Glenn A.
Adviser	:	Engr. Emmanuel Longares
School	:	De La Salle University – Dasmariñas
Pages	:	51 DO - INFORMATION
Year		2007 – 2008
Degree	A ZMG	Bachelor of Science in Electronics and Communications Engineering

The dog repeller device with stun gun will serve as a personal selfdefense device against stray and hostile dogs and assailants. The dog repeller device will produce ultrasonic sounds that will irritate or agitate the dogs' sensitive auditory senses. The ultrasonic frequency being emitted by the device will not cause any harm to humans' because it is inaudible to humans' auditory senses. The stun gun mode of the device will be used as a protection against assailants or those people that will inflict harm to the person who will be using the device. The stun gun will emit a high voltage shock enough to stun a person for seconds.

The shock produced by the device is not lethal because it has a very low current shock. The dog repeller with stun gun device will be a good help to people whose activities are outdoor and also to those people who are afraid to be bitten by dogs.